



MCR PROXIMITY READERS



MCR-50-H

MCR-64-H

MCR-30-H



MCR Proximity Readers



Frequency: 125 kHz

Read Ranges:

MCR-30-H: Up to 3.5 inches (88 mm)

MCR-50-H: Up to 7 inches (176 mm)

MCR-64-H: Up to 7 inches (176 mm)



ETL Listed

Independently Tested and Certified to Conform to UL Standard 294



Warranty

Lifetime Warranty



Wiegand

Output Interface



Contactless

Up to 7 in (176 mm)



Mullion Mount (MCR-30-H)

Metal Door, Window Frames & Flat Surfaces



U.S. Single-Gang Wall-Box Mount (MCR-50-H and MCR-64-H)

Metal or Plastic Box & Flat Surfaces

MCR PROXIMITY READERS

The MCR Proximity Readers are specialty readers within the *Pyramid Series Proximity*[®] family of readers. Making use of proven digital radio frequency identification (RFID) technology, they support certain Indala[®] ASP Advantage Series Proximity formats, certain HID[®] 125-kHz proximity protocol, and Pyramid series 125-kHz proximity protocol. Allowing for both indoor and outdoor operation, the electronics are secured in tamper-resistant epoxy potting.

Specifications	MCR-30-H	MCR-50-H	MCR-64-H
Technology	Proximity		
Frequency	125 kHz		
Mounting	Mullions, including metal door and window frames, as well as flat surfaces	Metal or plastic US single-gang wall box, as well as flat surfaces	Metal or plastic US single-gang wall box, as well as flat surfaces
Dimensions	1.7" W × 3.2" H × 0.7" D (43 mm × 81 mm × 18 mm)	3" W × 4.6" H × 0.4" D (76 mm × 117 mm × 10 mm)	3" W × 4.6" H × 0.75" D (76 mm × 117 mm × 19 mm)
OEM Label Area Dimensions	0.9" W × 0.35" H (22.86 mm × 8.89 mm) with corner radius of 0.63" (16 mm)		
Weight	3 oz (85 g)	4 oz (113 g)	4 oz (113 g)
Certifications	FCC, ICC, CE, UL Standard 294 ¹		
IP Code ²	IP67		
Voltage ³	+5 – 16 VDC		
Current Draw	0.07 to 0.085A	0.07 to 0.085A	0.085 to 0.125A
Read Range ⁴	Up to 3.5 inches (88 mm)	Up to 7 inches (176 mm)	Up to 7 inches (176 mm)
Cablings ⁵	24 AWG minimum, multiconductor stranded with an overall foil shield		
Interface	Wiegand		
Operating Temperature	–40° F to 149° F (–40° C to +65° C)		
Color Options	Black snap-on cover included standard		
Audio Tone	Beeper included standard		
Indoor & Outdoor Installation	Electronics sealed in weather- and tamper-resistant epoxy potting		
Warranty	Limited lifetime warranty		
LED	Four-state standard (red, green, amber, and off)		
Keypad Output ⁶	N/A	N/A	Wiegand
Technologies Supported	Certain Indala [®] ASP formats ⁷ + certain HID [®] 125-kHz Proximity protocols ⁸ + native Pyramid 125-kHz Proximity protocols ⁹		

NOTES:

- 1 Carrying the ETL Label and tested by Intertek, conforms to UL Standard 294.
- 2 Self evaluated.
- 3 Linear power supplies are recommended for best operation.
- 4 Using PSC-1 Standard Light Proximity Card with 12 VDC at the reader.
- 5 For example, Belden 9535 or similar.
- 6 Available only on MCR-64 model; 8-Bit Burst Wiegand standard. For 4-Bit Burst and other options, please contact Farpointe Data, Inc. Features may vary based on model.
- 7 Examples may include, and may not be limited to, Indala[®] 26-bit 1L, Indala[®] 27-bit 1L, Indala[®] Scrambled 27-bit 1L, and Indala[®] 32-bit 1L. For additional formats, contact Farpointe Data, Inc.
- 8 Examples may include, and may not be limited to, ProxCard II[®], ISOProx[®] II, and ProxKey[®] II.
- 9 Examples may include, and may not be limited to, PSC-1, PSI-4, PSM-2, PSK-3, and PDT-1.

Farpointe Data reserves the right to change specifications without notice.



© 2004-2016 Farpointe Data, Inc. All rights reserved. Farpointe Data[®], Pyramid Series Proximity[®], Delta[®], and Ranger[®] are the registered U.S. trademarks of Farpointe Data, Inc. HID, the HID logo, Indala, ProxCard II, ISOProx, and ProxKey are registered trademarks of HID Global Corporation, an ASSA ABLOY company. All other trademarks are the property of their respective owners.

www.farpointedata.com

Farpointe Data, Inc.
1376 Borregas Avenue
Sunnyvale, CA 94089-1004 USA
Office: +1-408-731-8700
Fax: +1-408-731-8705
support@farpointedata.com