



P-410 GUARDIAN PROXIMITY READER



Guardian Vandal Resistant



Frequency: 125 kHz
Read Range: Up to 8 inches (202 mm)



MAXSecure™
Unique Security Feature



fleaPower™
Energy-Conservation Technology



Pro-X™
Read-Range Boosting Technology



Warranty
Lifetime Warranty



Wiegand
Output Interface



U.S. Double-Gang Wall-Box Mount
Metal or Plastic Box & Flat Surfaces



Vandal Resistant
Impact Resistant

P-410 GUARDIAN PROXIMITY READER

Guardian vandal-resistant readers are manufactured from thick polycarbonate material, feature epoxy potted electronics, and ship standard with tamperproof screws. Guardian readers are ideal for installations where more durability is required than the standard proximity reader. Such installations include schools, inner-city environments, correctional facilities, or sites where heavy machinery is operated.

Specifications	P-410
Technology	Proximity
Frequency	125 kHz
Mounting	Metal or plastic US double-gang wall box, as well as flat surfaces
Dimensions	5" H x 5" W x 1" D (127 mm x 127 mm x 25 mm)
OEM Label Area Dimensions	0.9" H x 0.35" W (22.86 mm x 8.89 mm) with corner radius of 0.06" (1.5 mm)
Weight	13 oz (369 g)
Certifications	FCC, ICC, CE
IP Code ¹	IP67
Voltage ²	+5 – 16 VDC
Current Draw	35 mA typical, 75 mA peak @ 12 VDC
Read Range ³	Up to 8 inches (202 mm)
Cabling ⁴	24 AWG minimum, multiconductor stranded with an overall foil shield
Interface	Wiegand ABA Track II
Operating Temperature	-40° F to 149° F (-40° C to +65° C)
Color Options	Black
Audio Tone	Beeper included standard
Indoor & Outdoor Installation	Electronics sealed in weather- and tamper-resistant epoxy potting
Warranty	Limited lifetime warranty
LED	Four-state standard (red, green, amber, and off)
Technologies Supported	P-410: <i>Pyramid Series Proximity</i> ® Cards and Tags ⁵ P-410-H: Pyramid + certain HID® 125-kHz Proximity protocols ⁶ P-410-A: Pyramid + certain AWID® 125-kHz Proximity protocols ⁷ P-410-H-A: Pyramid + certain HID® 125-kHz Proximity protocols + certain AWID® 125-kHz Proximity protocols

NOTES:

- 1 Self evaluated.
- 2 Linear power supplies are recommended for best operation.
- 3 Using PSC-1 Standard Light Proximity Card with 12 VDC at the reader.
- 4 For example, Belden 9535 or similar, supporting the five conductors comprising the physical layer of the Wiegand interface (power, ground, data 0, data 1, and/or beeper and LED). Alternatively, Belden 9539 or similar, for all reader functions. Contact your access control system manufacturer for their specific requirements.
- 5 Examples may include, and may not be limited to, PSC-1, PSI-4, PSM-2, PSK-3, and PDT-1.
- 6 Examples may include, and may not be limited to, ProxCard II®, ISOProx® II, and ProxKey® II.
- 7 Examples may include, and may not be limited to, CS Prox Card, GR (ISO) Graphics Quality Prox Card, and KT Key Tag.

Farpointe Data reserves the right to change specifications without notice.



© 2012-2019 Farpointe Data, Inc. All rights reserved. Farpointe Data®, Pyramid Series Proximity®, Delta®, and Ranger® are the registered U.S. trademarks of Farpointe Data, Inc. Conekt is a trademark of Farpointe Data, Inc. AWID is a registered trademark of Applied Wireless Identifications Group. HID, the HID logo, ProxCard II, ISOProx, and ProxKey are registered trademarks of HID Global Corporation, an ASSA ABLOY company. All other trademarks are the property of their respective owners.

www.farpointedata.com

Farpointe Data, Inc.
 2195 Zanker Road
 San Jose, CA 95131 USA
 Office: +1-408-731-8700
 Fax: +1-408-731-8705
support@farpointedata.com