



WRT-2M

MINI LONG-RANGE TRANSMITTER



Ranger[®] Long-Range



BUTTON PRESS:

Frequency: 433 MHz

Read Range: Up to 150 feet (46 m)



MAXSecure™

Unique Security Feature



Warranty

One-Year Warranty



Wiegand

Output Interface



Slot-Punch

Built-in Eyelet



Contactless

Button Press – Up to 150 ft (46 m)

WRT-2M MINI LONG-RANGE TRANSMITTER

Ranger from Farpointe Data sets the electronic security benchmark for high frequency, long-range identification Receivers and Transmitters. Based upon proven contactless digital ultra-high frequency (UHF) technology, the Ranger Receivers interface with a wide range of electronic access control systems by complying with the Wiegand communication protocol. They offer value-add features such as MAXSecure™ and up to 150 feet of read range (WRT-2M with WRR-44). The WRT-2M Transmitter is an active device, powered by a highly reliable and common battery, and can be fitted with an adhesive disc tag, such as Farpointe's model PDT-1—that adheres to the back of the Transmitter—which also allows it to be used as a close-range presentation-style access credential. Disc tags, which are sold separately, are available in a variety of protocols.

Specifications	WRT-2M
Technology	Long range
Frequency	Button press: 433 MHz
Marking	Date code and ID
Dimensions	1.4" W × 1.95" H × 0.47" D (35.6 mm × 49.5 mm × 11.9 mm)
Button Press Transmission	Rolling code + encryption
Weight	0.6 oz (17 g)
Certifications	FCC, ICC, CE
IP Code ¹	IP65
Battery ²	Single replaceable CR2032, 3.3V, lithium battery
Compatibility	Button press: WRR-44 and WRR-22 Receivers
Read Range ³	Upon button press: WRR-22: Up to 75 feet (23 m) WRR-44: Up to 150 feet (46 m)
Durability ⁴	Electronics sealed in a weather-resistant enclosure
Interface ⁵	Wiegand (26-bit industry standard and custom Wiegand formats)
Operating Temperature	−40° F to 122° F (−40° C to +50° C)
Enclosure	Black polycarbonate
Buttons	Red silicon
OEM Label Area Dimensions	0.9" W × 0.35" H (22.86 mm × 8.89 mm), with corner radius of 0.06" (1.5 mm)
Key Ring	Optional 1-inch (25 mm) key ring
Warranty	1-year limited warranty
Convenience	Built-in eyelet makes it easy to carry on a key ring or lanyard
LED	Integrated red LED standard (activated upon button press)
Presentation Disc Tag (sold separately)	PDT-1: <i>Pyramid Series Proximity</i> ® supported ⁷ PDT-1-A: Certain AWID® 125-kHz Proximity protocols supported PDT-1-H: Certain HID® 125-kHz Proximity protocols supported ⁸
Technologies Supported ⁶	

NOTES:

- 1 Self evaluated.
- 2 Rated to typically provide more than 250,000 button presses under normal conditions with supplied Renata CR2032.
- 3 Button press tested with 12 VDC at WRR-22 and WRR-44. Receiver coverage is omni-directional and need not be installed in a line-of-sight configuration.
- 4 Electronics are snap sealed in a weather-resistant enclosure.
- 5 Please contact Farpointe for ordering assistance.
- 6 Presentation requires a separate disc tag, sold separately, such as the PDT-1 Disc Tag, which would be adhered to the back of the transmitter. When ordering, please indicate the proximity disc tag desired. Contact Farpointe for additional information.
- 7 Examples of supporting readers include, but are not limited to, P-300, P-400, P-500, and P-640.
- 8 Examples of supporting readers include, but are not limited to, ProxPoint® Plus, ThinLine II®, and MiniProx®.

Farpointe Data reserves the right to change specifications without notice.

© 2018 Farpointe Data, Inc. All rights reserved. Farpointe Data®, Pyramid Series Proximity®, Delta®, and Ranger® are the registered U.S. trademarks of Farpointe Data, Inc. MIFARE is a registered trademark of NXP B.V. AWID is a registered trademark of Applied Wireless Identifications Group. HID, the HID logo, ProxPoint, ThinLine II, and MiniProx are registered trademarks of HID Global Corporation, an ASSA ABLOY company. All other trademarks are the property of their respective owners.

www.farpointedata.com

Farpointe Data, Inc.
 1376 Borregas Avenue
 Sunnyvale, CA 94089-1004 USA
 Office: +1-408-731-8700
 Fax: +1-408-731-8705
support@farpointedata.com

