



CONEKT[®] SMARTCARD CREDENTIALS



CSC-2
Clamshell Card

CSK-2 Keyfob

CSM-2P and CSM-2S
ISO Cards



Conekt Mobile Smartphone Access Control Solution



Frequency: 13.56 MHz

Read Ranges:

CSC-2: Up to 2.25 inches (57 mm)

CSM-2P/S: Up to 2.25 inches (57 mm)

CSK-2: Up to 1 inch (25 mm)



MIFARE[®] DESFire[®] EV2 Support
High-Security Encryption Technology



MAXSecure[™]
Unique Security Feature



ValidID[™]
Fraudulent Data Detection Solution



Warranty
One-Year Warranty / Limited Lifetime Warranty



Wiegand
Output Interface



Slot-Punch
Vertical Slot / Vertical & Horizontal Indicators / Built-in Eyelet



Contactless
Up to 2.25 in (57 mm)

CONEKT® SMARTCARD CREDENTIALS

Conekt comprises Farpointe Data’s mobile-ready contactless smartcard access control ID solution. Based upon the proven LEGIC® contactless digital radio frequency identification (RFID) platform, Conekt readers interface with a wide range of electronic access control systems by complying with either the legacy Wiegand or bi-directional Open Supervised Device Protocol (OSDP). In addition to supporting mobile access credentials—using the Bluetooth Low Energy (BLE) feature of select smartphones—Conekt includes a range of traditional physical access credentials, such as clamshell cards, ISO cards, and key tags. Conekt’s range of credentials support 26-Bit Wiegand format, as well as custom Wiegand, ABA Track II magnetic stripe and serial data formats. They employ value-add features, such as MAXSecure™, and advanced data protection, such as AES encryption. All Conekt credentials can be ordered programmed to various formats in exact number sequence required, and can be private labeled with a company name, logo, phone number, web address, or other information.

Specifications	CSC-2	CSM-2P/S	CSK-2
Technology	Smartcard		
Frequency	Excitation (13.56 MHz)		
Operation	Passive (no battery)		
Type	Clamshell-style card	ISO-style card	Key fob-style tag
Formats	Wiegand (26-bit and custom formats) and ABA Track II magnetic stripe (clock and data)		
Material	ABS housing, PC sticker	PET composite surface + PVC core	ABS housing, stainless steel frame
Color	White	Glossy white	Grey
Slot Punch	Standard, vertical slot	Vertical and horizontal indicators	Built-in eyelet
Marking ¹	Date code and ID		
Imaging ²	Use a glossy adhesive overlay for color dye sublimation printing or print directly on card	Supports dye sublimation imaging	N/A
Read Range ³	Up to 2.25 inches (57 mm)	Up to 2.25 inches (57 mm)	Up to 1 inch (25 mm)
Outputs ⁴	Multi-Application		
Options ⁵	Custom printing of company logos, URL, telephone number, and more		
Warranty	Limited lifetime warranty	12 months	12 months
OEM Label Area Dimensions	0.9" W × 0.35" H (22.86 mm × 8.89 mm) with corner radius of 0.06" (1.5 mm)	N/A	0.9" W × 0.35" H (22.86 mm × 8.89 mm) with corner radius of 0.06" (1.5 mm)
Dimensions	2.1" W × 3.4" H × .07" D (54 mm × 86 mm × 1.8 mm)	2.1" W × 3.4" H × 0.03" D (54 mm × 86 mm × 0.76 mm)	1.9" W × 1.5" H × 0.28" D (49 mm × 38 mm × 7 mm)
Weight	0.35 oz (10 g)	0.23 oz (6.4 g)	0.39 oz (11 g)
Operating Temperature	-40° F to 158° F (-35° C to +70° C)	-31° F to 122° F (-35° C to +50° C)	-40° F to 158° F (-40° C to +70° C)
Humidity	0–95% non-condensing		N/A
Memory	2K memory standard ⁶		
ISO Standards	ISO 14443-A		
Technologies Supported	MIFARE® DESFire EV2		

NOTES:

- 1 Matching internal and external sequential coding standard. Custom printing available.
- 2 Please verify that the printer (or overlay) supports credential type/thickness.
- 3 Tested with 12 VDC @ Conekt CSR-35 reader.
- 4 Typical directory structure of up to 28 applications, with up to 32 files per application.
- 5 Contact Farpointe to learn how you can customize your cards and tags.
- 6 Other memory sizes available.

Farpointe Data reserves the right to change specifications without notice.

© 2018-2019 Farpointe Data, Inc. All rights reserved. Farpointe Data®, Pyramid Series Proximity®, Delta®, Ranger®, and CONEKT® are the registered U.S. trademarks of Farpointe Data, Inc. LEGIC is a registered trademark of LEGIC Identystems Ltd. MIFARE, MIFARE DESFire, MIFARE UltraLight, and MIFARE Plus are registered trademarks of NXP B.V. All other trademarks are the property of their respective owners.

Farpointe Data, Inc.
 2195 Zanker Road
 San Jose, CA 95131 USA
 Office: +1-408-731-8700
 Fax: +1-408-731-8705
 support@farpointedata.com

