



# DK1-3 KEY FOB SMARTCARD



## Delta<sup>®</sup> Contactless Smartcard



**Frequency:** 13.56 MHz  
**Read Range:** Up to 0.75 inches (19 mm)



**MAXSecure™**  
Unique Security Feature



**ValidID™**  
Fraudulent Data Detection Solution



**Warranty**  
Lifetime Warranty



**Wiegand**  
Output Interface



**Slot-Punch**  
Standard Reinforced Brass Eyelet



**Contactless**  
Up to 3 in (76 mm)

## DK1-3 KEY FOB SMARTCARD

Delta comprises Farpointe Data's 13.56 MHz line of contactless smartcard readers, cards, and tags. Based upon proven MIFARE® contactless digital radio frequency identification (RFID) technology, Delta readers interface with a wide range of electronic access control systems by complying with the Wiegand communication protocol. They offer value-add features such as MAXSecure™ and ValidID™. Additionally, Delta cards and tags are passive devices, eliminate maintenance by requiring no battery, and can be ordered programmed to various formats and encryption keys.

Specifications	DK1-3
Technology	Smartcard
Frequency	Excitation (13.56 MHz)
Operation	Passive (no battery)
Type	Key tag
Formats	Wiegand (26-bit and custom formats) and ABA Track II magnetic stripe (clock and data)
Material	ABS
Color	Gray
Slot Punch	Standard reinforced brass eyelet
Marking <sup>1</sup>	Date code and ID
Imaging <sup>2</sup>	N/A
Read Range <sup>3</sup>	Up to 0.75 inches (19 mm)
Outputs <sup>4</sup>	CSN and Sector
Options <sup>5</sup>	Custom printing of company logos, URL, telephone number, and more
Warranty	Limited lifetime warranty
OEM Label Area Dimensions	0.11" W × 0.25" H (2.8 mm × 6.4 mm) with corner radius of 0.63" (16 mm)
Dimensions	1.2" W × 1.5" H × 0.15" D (30 mm × 38 mm × 3.8 mm)
Weight	0.16 oz (4.5 g)
Operating Temperature	-35° F to 122° F (-37° C to +50° C)
Humidity	0-95% non-condensing
Memory	1K memory standard <sup>6</sup>
ISO Standards	Technology: ISO 14443 Size: N/A
Technologies Supported	MIFARE® Classic

### NOTES:

- 1 Matching internal and external sequential coding standard. Custom printing available.
- 2 Please verify that the printer (or overlay) supports credential type/thickness.
- 3 Tested with 12 VDC @ Delta5 reader. Reference Card Read Range Document for additional read range information.
- 4 CSN = Card Serial Number. Sector = access control data, such as format, facility code, and ID.
- 5 Contact Farpointe to learn how you can customize your cards and tags.
- 6 Other memory sizes available.

Farpointe Data reserves the right to change specifications without notice.

© 2012-2019 Farpointe Data, Inc. All rights reserved. Farpointe Data®, Pyramid Series Proximity®, Delta®, Ranger®, and CONEKT® are the registered U.S. trademarks of Farpointe Data, Inc. MIFARE is a registered trademark of NXP B.V. All other trademarks are the property of their respective owners.

**Farpointe Data, Inc.**  
 2195 Zanker Road  
 San Jose, CA 95131 USA  
 Office: +1-408-731-8700  
 Fax: +1-408-731-8705  
[support@farpointedata.com](mailto:support@farpointedata.com)

