



DK1-3 KEY FOB SMARTCARD



Delta[®] Contactless Smartcard



Frequency: 13.56 MHz
Read Range: Up to 0.75 inches (19 mm)



MAXSecure™
Unique Security Feature



ValidID™
Fraudulent Data Detection Solution



Warranty
Lifetime Warranty



Wiegand
Output Interface



Slot-Punch
Standard Reinforced Brass Eyelet



Contactless
Up to 3 in (76 mm)

DK1-3 KEY FOB SMARTCARD

Delta comprises Farpointe Data's 13.56 MHz line of contactless smartcard readers, cards, and tags. Based upon proven MIFARE® contactless digital radio frequency identification (RFID) technology, Delta readers interface with a wide range of electronic access control systems by complying with the Wiegand communication protocol. They offer value-add features such as MAXSecure™ and ValidID™. Additionally, Delta cards and tags are passive devices, eliminate maintenance by requiring no battery, and can be ordered programmed to various formats and encryption keys.

Specifications	DK1-3
Technology	Smartcard
Frequency	Excitation (13.56 MHz)
Operation	Passive (no battery)
Type	Key tag
Formats	Wiegand (26-bit and custom formats) and ABA Track II magnetic stripe (clock and data)
Material	ABS
Color	Gray
Slot Punch	Standard reinforced brass eyelet
Marking ¹	Date code and ID
Imaging ²	N/A
Read Range ³	Up to 0.75 inches (19 mm)
Outputs ⁴	CSN and Sector
Options ⁵	Custom printing of company logos, URL, telephone number, and more
Warranty	Limited lifetime warranty
OEM Label Area Dimensions	0.11" W × 0.25" H (2.8 mm × 6.4 mm) with corner radius of 0.63" (16 mm)
Dimensions	1.2" W × 1.5" H × 0.15" D (30 mm × 38 mm × 3.8 mm)
Weight	0.16 oz (4.5 g)
Operating Temperature	-35° F to 122° F (-37° C to +50° C)
Humidity	0-95% non-condensing
Memory	1K memory standard ⁶
ISO Standards	Technology: ISO 14443 Size: N/A
Technologies Supported ⁷	MIFARE® Classic

NOTES:

- 1 Matching internal and external sequential coding standard. Custom printing available.
- 2 Please verify that the printer (or overlay) supports credential type/thickness.
- 3 Tested with 12 VDC @ Delta5 reader. Reference Card Read Range Document for additional read range information.
- 4 CSN = Card Serial Number. Sector = access control data, such as format, facility code, and ID.
- 5 Contact Farpointe to learn how you can customize your cards and tags.
- 6 Other memory sizes available.
- 7 For security-relevant physical credential applications, users should consider MIFARE® DESFire®-based product families, such as CONEKT®.

Farpointe Data reserves the right to change specifications without notice.

© 2012-2024 Farpointe Data, Inc. All rights reserved. Farpointe Data®, *Pyramid Series* Proximity®, Delta®, Ranger®, and CONEKT® are the registered U.S. trademarks of Farpointe Data, Inc. MIFARE and MIFARE DESFire are registered trademarks of NXP B.V. All other trademarks are the property of their respective owners.

Farpointe Data, Inc.
 2195 Zanker Road
 San Jose, CA 95131 USA
 Office: +1-408-731-8700
 Fax: +1-408-731-8705
 support@farpointedata.com

