



# CREDENTIAL ORDER FORM

## CONTACT INFORMATION

Name: \_\_\_\_\_ Date: \_\_\_\_\_

Company Name: \_\_\_\_\_

Phone: \_\_\_\_\_ Email: \_\_\_\_\_

## PRODUCT SELECTION *(check one)*

<p><b>125-kHz Proximity</b> <i>Pyramid Series Proximity<sup>®</sup> Supported<sup>1</sup></i></p> <p><input type="checkbox"/> PSC-1 <input type="checkbox"/> PSI-4 <input type="checkbox"/> PSM-2P <input type="checkbox"/> PSM-2S <input type="checkbox"/> PSK-3 <input type="checkbox"/> PDT-1 <input type="checkbox"/> WRT-2+ <input type="checkbox"/> WRT-4+</p> <p><b>Certain AWID Proximity Protocols Supported<sup>2</sup></b></p> <p><input type="checkbox"/> PSC-1-A <input type="checkbox"/> PSI-4-A <input type="checkbox"/> PSM-2P-A <input type="checkbox"/> PSM-2S-A <input type="checkbox"/> PSK-3-A <input type="checkbox"/> PDT-1-A <input type="checkbox"/> WRT-2-A <input type="checkbox"/> WRT-4-A</p> <p><b>Certain HID<sup>®</sup> Proximity Protocols Supported<sup>3</sup></b></p> <p><input type="checkbox"/> PSC-1-H <input type="checkbox"/> PSI-4-H <input type="checkbox"/> PSM-2P-H <input type="checkbox"/> PSM-2S-H <input type="checkbox"/> PSK-3-H <input type="checkbox"/> PDT-1-H <input type="checkbox"/> WRT-2-H <input type="checkbox"/> WRT-4-H</p>	<p><b>13.56-MHz MIFARE<sup>®</sup> Smartcard Classic</b></p> <p><b>Delta<sup>®</sup> Smartcard 1K-byte Memory</b></p> <p><input type="checkbox"/> DC1-1 <input type="checkbox"/> DM1-3 <input type="checkbox"/> DM1-3S <input type="checkbox"/> DK1-3 <input type="checkbox"/> WRT-2+S1 <input type="checkbox"/> WRT-4+S1</p> <p><b>Delta<sup>®</sup> Smartcard 4K-byte Memory</b></p> <p><input type="checkbox"/> DC4-1 <input type="checkbox"/> DM4-3 <input type="checkbox"/> DM4-3S <input type="checkbox"/> DK4-3 <input type="checkbox"/> WRT-2+S4 <input type="checkbox"/> WRT-4+S4</p>
<p><b>433-MHz Long Range</b> <i>Ranger<sup>®</sup> Receivers &amp; Transmitters</i></p> <p><input type="checkbox"/> WRT-2+ <input type="checkbox"/> WRT-4+ <input type="checkbox"/> WRT-2M</p>	<p><b>13.56-MHz MIFARE<sup>®</sup> DESFire<sup>®</sup> EV1 and EV2</b> <b>Delta<sup>®</sup> Smartcard 2K-byte Memory</b></p> <p><input type="checkbox"/> DE2</p> <p><b>CONEXT<sup>®</sup> Smartcard 2K-byte Memory</b></p> <p><input type="checkbox"/> CSC-2 <input type="checkbox"/> CSK-2</p> <p><input type="checkbox"/> CSM-2P <input type="checkbox"/> CSM-2S</p>

## PROGRAMMING DETAILS

26-bit Wiegand:

Yes Facility Code: \_\_\_\_\_ ID Range: \_\_\_\_\_  
 No

Other Format *(if applicable)*:

Format: \_\_\_\_\_ Facility Code: \_\_\_\_\_ ID Range: \_\_\_\_\_ Other: \_\_\_\_\_

## CARD NUMBERING

- Sequential Matching Internal/External
- No External Card Numbering
- Sequential Internal/Sequential Non-Matching External

If non-matching selected:

Internal Card Number Start: \_\_\_\_\_ Stop: \_\_\_\_\_

External Card Number Start: \_\_\_\_\_ Stop: \_\_\_\_\_

**MAXSecure™<sup>4</sup>**

Enabled:

- Yes                                      If yes, specify MAXSecure™ codes to be supported: \_\_\_\_\_
- No

**CARD MARKING**

NOTE: If this section is not completed, Farpointe will proceed as if no preference is selected.

- No Preference (*typically results in quickest lead time*)
- Laser
- Inkjet


**LASER ETCHED ARTWORK<sup>5</sup>**

- Yes                                      If yes, specify custom credential number: \_\_\_\_\_
- No

**SLOT PUNCH (if applicable)**

NOTE: Slot-punch only available for PVC printable credentials.

- Yes                                      If yes,  Horizontal  Vertical
- No



**NOTES:**

- 1 Examples of supporting readers include, but are not limited to, P-300, P-400, P-500, and P-640.
- 2 Examples of supporting readers may include, but are not limited to, SP-6820, Sr-2400, and kP-6840.
- 3 Examples of supporting readers may include, but are not limited to, ProxPoint®Plus, ThinLine II®, and miniProx®.
- 4 **MAXSecure** – MAXSecure is a programming feature that integrates a high-security handshake, or code, between card, tag and reader. MAXSecure can be used to increase the security of any data format, including the industry standard 26-Bit Wiegand format, custom Wiegand formats, as well as the ABA Track II magnetic stripe format. Please refer to the MAXSecure Code Request Form (P/N: 01590-001) for more information, or call Farpointe Data.
- 5 **Laser Etched Artwork** – a URL, short sentence or small logo may be laser etched on most credentials. Please refer to the Private Label Form (P/N: 01702-003) for more information, or call Farpointe Data.

Farpointe Data reserves the right to change specifications without notice.

© 2017-2019 Farpointe Data, Inc. All rights reserved. Farpointe Data®, Pyramid Series Proximity®, Delta®, Ranger®, and CONEKT® are the registered U.S. trademarks of Farpointe Data, Inc. MIFARE is a registered trademark of NXP B.V. AWID is a trademark of Applied Wireless Identifications Group. HID is a registered trademark of HID Global Corporation, an ASSA ABLOY company. All other trademarks are the property of their respective owners.

**Farpointe Data, Inc.**  
2195 Zanker Road  
San Jose, CA 95131 USA  
Office: +1-408-731-8700  
Fax: +1-408-731-8705  
support@farpointedata.com

